


# Satellite

# SE 867-AGPS GPS Standalone Embedded

Ultra Compact BGA Package High Sensitivity NMEA 0183 < 1m Position Accuracy \_ow Power Consumption WAAS, EGNOS and MSAS capable 44 Channel GPS Architecture A-GPS Ephemeris File Injection **RoHS Compliant** Extended Temperature Range





The new SE867-AGPS is the smallest module in Telit portfolio, and the first GPS standalone module featuring state-of-the-art GPS characteristics, with the high quality and great support that usually accompany Telit products.

The low profile and small size of the unique BGA package for the SE867-AGPS enable the design of extremely compact applications. Since connectors are eliminated, the solution cost is significantly reduced compared to conventional mounting.

With its ultra-compact design and extended temperature range, the Telit SE867-AGPS is the perfect module for high-volume m2m applications and mobile data devices.

Requiring only 2 layers for PCB design and little integration effort for external components, Telit SE867-AGPS represents the ideal solution in terms of total cost effectiveness and timeto-market readiness.

Equipped with a powerful yet power saving baseband processor, SE867-AGPS provides all the GPS information via NMEA standard protocol on serial interface.

Applications requiring extremely quick FIX can efficiently retrieve the correct position within two seconds, by means of assisted GPS and real-time ephemeris file injection.

As a part of Telit's corporate policy of environmental protection, all Telit products comply to the RoHS (Restriction of Hazardous Substances) directive of the European Union (EU Directive 2002/95/EG).

## Product features

- Dimensions: 18 x 18 x 3.5 mm
- Weight: 1.8 g
- 35 balls BGA package, requiring only 2 Layer PCB
- Frequency Band: L1Band, C/A Code
- Standards: NMEA, 3GPP AGPS performance requirements
- 44 Channel GPS architecture
- Sensitivity
  - Autonomous Cold Start Acquisition: -144 dBm
- Assisted Acquisition: -155 dBm
- Autonomous Tracking: -160 dBm
- Flexible power supply
- Wide range from 2.5 up to 4.2 V plus
- reference voltage for I/O (1.8 V, 3 V typ)
  Multiple input power for enhanced power saving (1.8 V, 3.0 V typ)

- Positional Accuracy (CEP50): Autonomous Positional Error < 1.0 m</li>
- Velocity Accuracy (30 m/s)
   Speed: < 0.05 m/s</li>
- Heading: < 0.2 deg Time To First Fix (50% @ -130 dBm)
  - Hot Start: 1.3 s - Cold Start: <35 s
- Power consumption
  - Acquisition: 75 mW
  - Tracking: 65 mW
- RoHS compliant
- Temperature Range
  - Operating temperature: -30 to +85
  - Storage temperature: -30 to +85

# Making machines talk.®

# SE867-AGPS **GPS Standalone**







actual size



Telit Communications S.p.A. Via Stazione di Prosecco, 5/B I-34010 Sgonico (Trieste), Italy Tel +39 040 4192 200 Fax +39 040 4192 289 E-Mail: EMEA@telit.com

Telit Wireless Solutions Inc. 3131 RDU Center Drive, Suite 135 Morrisville, NC 27560, USA Tel +1 888 846 9773 or +1 919 439 7977 Fax +1 888 846 9774 or +1 919 840 0337 E-Mail: NORTHAMERICA@telit.com

Telit Wireless Solutions Inc. Rua Cunha Gago, 700 - cj 81, Pinheiros São Paulo - SP, 05421001, Brazil Tel +55 11 2679 4654 Fax +55 11 2679 4654 E-Mail: LATINAMERICA@telit.com

Telit Wireless Solutions Co., Ltd. 9th Fl., Daewoo Securities Bld. 447 H. J. Jaewoo Securities Bit. 34-3 Yeouido-dong, Yeongdeungpo-gu Seoul 150-716, KOREA Tel +82 2 368 4600 Fax +82 2 368 4600 E-Mail: APAC@telit.com

## www.telit.com



#### Interfaces

- UART 4.8 230 k Baud Rate
- PPS for precise timing
- EGNOS, WAAS and MSAS capability embedded. Correction of positional errors due to ionospheric and orbital disturbances

RTC for efficient power management

### **Approvals and Conformity** Assessment

- CE mark
- IEC 60950 (2005)
- ETSI EN 300 440-2 (v.1.2.1)
- EN 301 489-3 (v.1.4.1)

#### Additional features

A-GPS: ephemeris file injection

## Order-No.

Please contact your Telit representative for order codes and all further information and additional details









[05.2010]