


GPS Active Antenna

GA-330

GA-330 is an ideal active GPS antenna for your embedded system applications. With 16 x 16 x 7.5 mm in size, it best fit into your GPS system with maximum performance, also an idea combination for all your GPS applications.




Key Features :

- Small form factor: 16 x 16 x 7.5 mm
- Lead-Free – RoHS/WEEE compliant
- High gain up to 16.5dB
- Low power consumption
- 100mm cable with I-Pex connector

Applications :

- Handheld devices
- Automotive and Marine Navigation
- Automotive Navigator Tracking
- Emergency Locator
- Geographic Surveying
- Personal Positioning
- Sporting and Recreation
- Embedded applications : PDA, DSC, Smart phone, UMPC, PND, MP4

Dimension :



TRANSYSTEM INC.

An A+ supplier of RF microwave & GPS products

**Ultimate
Antenna**

GA-330 Specifications

Item	Symbol	Specification	Unit	Note
Central Frequency	f_c	1575±3	MHz	
Output Impedance	Z_o	50	Ohm	At f_c
Antenna Gain	G_A	2.5	dB	Based on ground size 40x40mm size
LNA Gain	G_L	16.5	dB	At f_c , No SAW filter
Noise Figure	NF	1.5	dB	At f_c , 1.8dB Max.
In Band Flatness		1	dB	$\leq f_c \pm 1\text{MHz}$
Output VSWR		2.0 max		At f_c
Supply Voltage	V_{cc}	3.0±5%	Vdc	
Power Consumption	I_{cc}	<3	mA	
Operating Temperature	T_{op}	-30 ~ +85	°C	
Storage Temperature	T_s	-40 ~ +125	°C	
Operating Humidity		$\leq 95\%$		Non-condensing
Dimension		16 x 16 x 7.5	mm	

Note : 1. Standard testing conditions are 25°C, 3V V_{cc} , 65% RH
2. Specifications are subject to exterior case supplied by customer.

*Specifications subject to change without prior notice.
Copy right ©2009 TRANSYSTEM INC. all rights reserved.



No.1-2 Li-Hsin Rd.I, Science-Based
Industrial Park, Hsinchu, Taiwan
T: +886-3-5780393 / F: +886-3-5784111
gps.sales@transystem.com.tw