

## GSM | GPRS

### GM862-QUAD Modem

### GM862-QUAD-PY Modem



0101 0101	Telit Unified AT Command Set
4 GPRS	Quad Band GPRS
(+)	GPRS Class 10
Pin to Pin	Pin to Pin Backward Compatible
Leaf	RoHS Compliant
SIM	On Board SIM Holder
SIM	SIM Access Profile
Python	PYTHON* Script Interpreter
FTP/SMTP	Embedded FTP and SMTP Client
Thermometer	Extended Temperature Range
RF	Extended RF Sensitivity
Serial Port	Serial Port Multiplexer (GSM 7.10)
TCP/IP	Embedded TCP/IP Stack



The GM862-QUAD module is the next generation of the GM862 product family continuing Telit's success in the field of easy-to-integrate GSM/GPRS modules for all industrial m2m applications.

The development focus of the GM862-QUAD was on pin-to-pin compatibility to existing GM862 products, while adding quad-band functionality and RoHS compliance. This translates into one consistent product offering for global GSM networks and provides for significant cost advantages with the savings in approvals and logistics costs.

The ruggedized design, extended temperature range, and integrated SIM card holder make the GM862-QUAD the ideal platform for medium volume projects. Additional features like jamming detection, integrated TCP/IP protocol stack, and Telit's Easy Scan® functionality feature extend capabilities without adding cost.

The GM862-QUAD-PY makes it possible to run customer applications inside the module, thus making the device a complete platform for customer solutions. State-of-the-art IIC interfaces provide connectivity to external peripherals such as sensors and displays.

All Telit modules, support Over-the-Air firmware update by means Premium FOTA Management. By embedding RedBend's vCurrent® agent, a proven and battle-tested technology powering hundreds of millions of cellular handsets world-wide Telit is able to update its products by transmitting only a delta file, which represents the difference between one firmware version and another.

As a part of Telit's corporate policy of environmental protection, Telit products comply to the RoHS (Restriction of Hazardous Substances) directive of the European Union (EU Directive 2002/95/EG).

#### Product features


- Quad-band EGSM 850 / 900 / 1800 /1900 MHz
- Output power
  - Class 4 (2W) @ 850 / 900 MHz
  - Class 1 (1W) @ 1800 / 1900 MHz
- Control via AT commands according to GSM 07.05, 07.07 and Telit enhanced
- Supply voltage range: 3.22-4.5 V DC (3.8 V DC recommended)
- Power consumption (typical values)
  - Power off: 26 uA
  - Idle (registered, power saving): 2.6 mA
  - Dedicated mode: 200 mA
  - GPRS cl.10 (max): 370 mA
- Serial port multiplexer GSM 7.10
- SIM access profile
- Sensitivity:
  - 107 dBm (typ.) @ 850 / 900 MHz
  - 106 dBm (typ.) @ 1800 / 1900 MHz
- Dimensions: 43.9 x 43.9 x 6.9 mm
- Weight: 19 grams
- Extended temperature range
  - 40°C to +85°C (operational)
  - 40°C to +85°C (storage temperature)
- RoHS compliant
- TCP/IP stack access via AT commands

**GM862-QUAD**

Modem

**GM862-QUAD-PY**

Modem



actual size

**Interfaces**

- 50-pin Molex connector
- 13 I/O ports maximum
- Analog audio (balanced and unbalanced)
- 1 A/D converter
- Buzzer output
- ITU-T V.24 serial link through UART:
  - CMOS level
  - Baud rate from 300 to 115,200 bps
  - Autobauding from 2,400 to 57,600 bps
- 50 Ohm MMCX antenna connector
- On board SIM card holder, 1.8 V / 3 V with real-time detection

**Audio**

- Telephony, emergency call
- Half rate, full rate, enhanced full rate and adaptive multi rate voice codecs (HR, FR, EFR, AMR)
- Superior echo cancellation & noise reduction
- Handset & hands-free operations
- DTMF

**Approvals**

- Fully type approved conforming with R&TTE directive
- CE, FCC, IC, GCF, PTCRB, Anatel

**SMS**

- Point-to-point mobile originated and mobile terminated SMS
- Concatenated SMS supported
- SMS cell broadcast
- Text and PDU mode

**Circuit switched data transmission**

- Asynchronous transparent circuit switched data (CSD) up to 14.4 kbps
- Asynchronous non-transparent CSD up to 9.6 kbps
- V.110

**GPRS data**

- GPRS class 10
- Mobile station class B
- Coding scheme 1 to 4
- PBCCH support

**Fax**

- Group 3, class 1

**GSM supplementary**

- Call forwarding
- Call barring
- Call waiting & call hold
- Advice of charge
- Calling line identification presentation (CLIP)
- Calling line identification restriction (CLIR)
- Unstructured supplementary services mobile originated data (USSD)
- Closed user group

**Additional features**

- SIM phonebook
- Fixed dialing number (FDN)
- Real-time clock
- Alarm management
- Battery management
- Network LED support
- IRA character set
- Jamming detection & report
- Embedded TCP/IP stack, including TCP, IP, UDP, SMTP and FTP protocols
- TFMS (Telit Firmware Management Services) Over-the-Air update

**Python\* application resources (GM862-QUAD-PY ONLY)**

- Python\* script interpreter (module takes application code directly in the Python\* language)
- Memory: 1.9 MB of NV memory for the user scripts and 1.2 MB RAM for the Python\* engine usage
- Over-the-air application SW update
- IIC Bus and SPI Bus controlled in Python\*

**Telit's EASY features**

- EASY SCAN® automatic scan over GSM frequencies (with or without SIM card)

**Order-No.**

Please contact your Telit representative for order codes and all further information



Telit Communications S.p.A.  
Via Stazione di Prosecco, 5/B  
I-34010 Sgonico (Trieste), Italy  
Tel +39 040 4192 200  
Fax +39 040 4192 289  
E-Mail: EMEA@telit.com

Telit Wireless Solutions Inc.  
3131 RDU Center Drive, Suite 135  
Morrisville, NC 27560, USA  
Tel +1 888 846 9773 or +1 919 439 7977  
Fax +1 888 846 9774 or +1 919 840 0337  
E-Mail: NORTHAMERICA@telit.com

Telit Wireless Solutions Inc.  
Rua Cunha Gago, 700 - cj 81, Pinheiros  
São Paulo - SP, 05421001, Brazil  
Tel +55 11 2679 4654  
Fax +55 11 2679 4654  
E-Mail: LATINAMERICA@telit.com

Telit Wireless Solutions Co., Ltd.  
9th Fl., Daewoo Securities Bld.  
34-3 Yeouido-dong, Yeongdeungpo-gu  
Seoul 150-716, KOREA  
Tel +82 2 368 4600  
Fax +82 2 368 4606  
E-Mail: APAC@telit.com

www.telit.com

Distributed by:

Copyright © 2009, Telit Communications S.p.A. - Subject to changes in technology, design and availability

\* Copyright © 1991-1995 by Stichting Mathematisch Centrum, Amsterdam, The Netherlands; All Rights Reserved.  
Copyright © 1995-2001 Corporation for National Research Initiatives; All Rights Reserved.  
Copyright © 2001-2009 Python Software Foundation; All Rights Reserved.  
All Rights Reserved are retained in Python.